


ProArt Display PA328CGV



Key Features



WQHD
2560x1440

Supporting WQHD 2560 x 1440 resolution for crystal clear image quality



Up to 600 nits brightness with HDR for lifelike contrast & color that brings out details like never before



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle

165Hz

Rapid Refresh Rate

Decimating blurry and delivers smooth and crisp video rendering



Up to 95% DCI-P3 international color standard of digital cinema industry



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the ΔE color difference value is less than 2



USB Type-C Monitor

USB-C connection for DisplayPort, USB data transmission and supports 90W power delivery



Desk Mount Kit

A convenient mounting clamp is included to help free up desk space




4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

ASUS

ProArt Display PA38CGV

Spec Sheet

Display	Panel Size : 32-inch (81.28cm) Wide Screen (16:9) Display Viewing Area(HxV) : 708.48 x 398.52 mm Panel Backlight / Type : IPS True Resolution : 2560 x 1440 Pixel Pitch : 0.277 mm Display Colors : 1073.7M (10 bit) Color Saturation : 95% DCI-P3, 100% sRGB/Rec.709 Brightness : 450 cd/m ² (typical), 600 cd/m ² (peak) Contrast Ratio: 1000:1 (typical) ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR≥10) : 178° (H)/178° (V) Response Time : 5ms (GTG) Flicker-free : Yes HDR support : Yes, HDR-10 Refresh Rate (Max) : 165Hz	
Video Feature	Trace Free Technology : Yes ProArt Preset : 10 modes (Standard / sRGB / Rec. 709 / DCI-P3 / Rapid Rendering / HDR / Scenery / Reading / User mode1 / User mode2) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes Gamma Adjustment : Yes (Support Gamma 2.6, 2.4, 2.2, 2.0, and 1.8) Color Adjustment : 6-axis (R, G, B, C, M, Y) Color Temperature Selection : 5 modes Picture-in-Picture : Yes Picture-by-Picture : Yes (support up to 2 windows) QuickFit+: Yes (Center Marker / Safety Area / Ruler / Customization) HDCP support : Yes, 2.2 FreeSync Premium Pro support: Yes (48 ~ 165Hz)	
Audio Feature	2W x 2 stereo, RMS	
IO ports	Signal Input: DisplayPort1.4 x 1 HDMI (v2.0) x 2 USB-C x 1 (90W PD)	Earphone Jack : Yes (3.5mm Mini-jack) USB Hub: 4x USB 3.2 Gen 1 Type-A
		
Signal Frequency	Digital Signal Frequency : HDMI: 30~222 KHz (H) / 48~144 Hz (V) USB-C, DisplayPort: 30~250 KHz (H) / 48~165 Hz (V)	
Power Consumption	Power On (Typical): <28W Power Saving Mode : < 0.5W ; Power Off Mode : 0.5W (Hard Switch) 100~240V, 50/60Hz	
Mechanical Design	Tilt : +23° ~ -5° Swivel : +30° ~ -30° Pivot : 90° (Clockwise& Anticlockwise)	Height Adjustment : 0 ~ 130 mm VESA Wall Mounting : 100 x 100 mm Desk C-Clamp Support
Dimensions	Phys. Dimension with Stand (WxHxD) : 727.08 x (471.48~601.48) x 245 mm Phys. Dimension without Stand (WxHxD) : 727.08 x 428.13 x 67.72 mm Box Dimension (WxHxD) : 840 x 516 x 280 mm	
Weight	Net Weight (Esti.) : 11.7 Kg, Without Stand (Esti.) : 7.15 Kg, Gross Weight (Esti.) : 16.8 Kg	
Accessories	Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), USB-C to USB-A cable (optional), Desk C-Clamp, Calibration Report, Quick Start Guide, Warranty Card, Welcome Card	
Compliance Standard	Energy Star®, FCC, UL/cUL, cTUVus, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, CECP, BSMI, Taiwan Energy Label, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, SDoC, e-Standby, PSB, BIS, VN MEPS, TCO, RoHS, NOM, CEC, WHQL Windows 7/8.1/10, EPEAT Bronze, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified, VESA DisplayHDR 600	

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice

ASUS